

PROXIMITY CARD WITH INCORPORATED
PIN CODE PROTECTION

[001] This application is a continuation-in-part application of Serial No. 09/397,269, filed September 16, 1999.

Field of the Invention:

[002] The field of the invention is that of an electronic security systems, particularly those in which a user carries a credential device, usually in the form of a proximity card, bearing identification data.

BACKGROUND OF THE INVENTION

[003] A shortcoming of prior art securing systems which use a card or similar device for identification of the bearer, is that the wrong person may gain control of the card. To guard against this risk, the proper bearer is assigned a personal identification number (PIN) code which must be included with the card for proper use. This number is typically known only to one or a very few people. The PIN code is analogous to the personal code used to operate an automatic teller machine. The PIN code is typically entered through a key pad mounted on or near the door frame.

[004] Other inventions have introduced the concept of requiring a PIN code entry at the time of use. Some of these efforts require a keyboard mounted at the entry, thus spoiling the architecturally desirable feature of proximity systems, namely having no unwanted elements on the entry portal. These efforts are in part covered by patents listed in the second group, References 6 through 11 below. This group has the disadvantage of not being proximity and thus requiring mechanical reading equipment for accomplishing the intended use.

[005] Reference #1, Patent 4,236,068, has a keyboard on the card and has the convenience of proximity, but does not include the PIN feature. References 1 to 5 cover proximity but do not have the PIN code concept included. References 1 to 5 refer to multiple earlier patents on proximity systems, which are by now

well established and known in the art. The References 1 to 5 provide ample proximity knowledge. References 6 through 11 provide patent background information on card and credential systems in which a PIN code is introduced.

REFERENCES AND PRIOR ART

[006] The personal identification and signaling system of U.S. Patent 4,223,830, shows a card with a button and various means for modulating and demodulating identifying data, and coupling this data to a reader and hence to a computer or communication system. This patent fails, however, to show entry of a PIN number to enable the card.

[007] Figure 1 of Reference Patent #1 4,223,830 illustrates the card with an included antenna, battery, crystal and display.

	<u>Number</u>	<u>Abbreviated Descriptive Title</u>
Reference 1	4,223,830	Identification System with Dual Data Frequencies
Reference 2	4,236,068	Personal Identification with Multiple Data Frequencies and Emergency Bits
Reference 3	4,384,288	Pulse Position Modulation
Reference 4	4,459,474	Direction, Differential
Reference 5	4,473,825	Power I/O, Plus

[008] The group of patents covered by Reference 1 to Reference 5 show various methods of coupling data from the card, via antennas on both the card and the reader, to the reader, and hence to computer and communication systems. This is established art and provides several means for the subject invention to accomplish the identification data transfer through the proximity coupling function. These first five references list Charles Walton as the inventor.

	<u>Number</u>	<u>Abbreviated Descriptive Title</u>
Reference 6	5,559,507	Signal Transmission and Tag Reading for Inductive Reader
Reference 7	5,883,603	Implantable Biosensing Transponder
Reference 8	5,874,896	Electronic Anti Shop Lifting System for RFID Tag
Reference 9	5,847,662	Radio Card Communication Apparatus

[009] References 6 through 9 are other examples of proximity identification art by other inventors, but none have the added security of requiring entry of a PIN code before use, so that any unauthorized person gaining control of the card could achieve unauthorized entry.

	<u>Number</u>	<u>Abbreviated Descriptive Title</u>
Reference 10	4,614,861	Unitary Self Contained Card Verification and Validation
Reference 11	4,853,522	Access to Data Field with Multiple Services
Reference 12	4,965,568	Multilevel Security with Personal Key
Reference 13	5,561,706	Managing access with a Billing Code
Reference 14	5,627,355	Transaction Device Protecting Account Numbers
Reference 15	5,694,471	Counterfeit-Proof Identification Card

[010] The patents References 10 through 15 show means of introducing a PIN code into a hand held object such as a card, but fail to incorporate the proximity sensing feature. These patents do not solve the problem of both being easy to use, through proximity, and being secure.

SUMMARY OF THE INVENTION

[011] The deficiencies of the prior art are overcome by the present invention which includes a proximity reader and card, using known proximity data coupling techniques. That is, the reader stimulates the card, causing the card to cycle through its data functions, and the data stored in the card is transferred to the reader. This invention adds to the card a keyboard, or data entry means, from which a sub group of digits can be entered into the card. When the PIN is entered into the card through the use of the keyboard, the PIN is compared to a previously stored internal reference PIN. If the two PINS agree, normal proximity data transfer is allowed to occur, and the bearer of the card is properly identified. If the internal reference PIN and the entered PIN do not agree, normal identification is denied. In other words, the bearer must have prior knowledge which establishes that he is the proper owner of the card. The system can also be mounted in a hand held or lap top computer and the computer keyboard used to enter the PIN. The system can also be mounted in a cell phone, and use the cell phone keyboard for entry of the PIN, and have the proximity loop antenna built into the phone.

[012] In one embodiment of the present invention, the correct comparison between the entered PIN and the internal PIN would result in the transfer of information provided within the card to an external, proximity device close to, but not touching the card. This system would be used to allow the bearer of the card to be admitted to a particular area.

[013] The system is secure because only the authorized bearer of the card is allowed admission to this area. More particularly, the method of card identification is known as proximity, meaning that the user need only hold the identification card near to a reader and identification is accomplished. The card need not be removed from a wallet or handbag to accomplish this identification function, provided the necessary personal identification number has been entered into the card. This invention is also in the category of security in

which steps are taken to be certain that the proper person has control of the identification card, by requiring a PIN known only by the user to be entered into the card entry by the user.

[014] Another embodiment of the present invention allows the proximity card to be used to activate electrical or mechanical devices. For example, the proximity card may be used to operate a firearm, only when the proper PIN is entered into the card. If this occurs, a signal would be sent to the firearm to release the safety.

[015] Yet another embodiment of the present invention includes the use of the card being directly inserted into the slot of a card reader. After the PIN is entered by the bearer of the card, it would be inserted into the card reader. A comparison is made between the entered PIN and an internal PIN provided in the memory of the card. When inserted into the slot, a successful comparison of the two PINs would allow various operations to occur, such as the opening of a portal and/or the activation of various mechanical or electrical equipment.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2

BRIEF DESCRIPTION OF THE DRAWINGS

[16] FIGURE 1 shows the appearance of one form of the card, bearing the keyboard;

[017] FIGURE 2 shows the internal block diagram of the card;

[018] FIGURE 3 shows a readers block diagram;

[019] FIGURE 4 shows a hand held computer incorporating PIN data transfer circuits;

[020] FIGURE 5 shows a second view of a hand held computer incorporating PIN data transfer;

[021] FIGURE 6 shows the card being inserted into a card reader; and

[022] FIGURE 7 shows a modification of the diagram shown in Figure 3.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[023] Figure 1 illustrates an identification card used in the present invention. The typical size of this identification card 2, sometimes referred to as a "credential", will be that of a conventional credit card, such as 9 cm by 5.5 cm. This first preferred embodiment of the present invention is in the form of a card based on proximity technology. This technology allows the card to serve as a data source, or incorporate a data source, with the data communicated first to a reader and from the reader to any higher level processor, such as a central computer. The data to be transferred includes elements such as: an employee number, a unique personal identification number, an emergency number, and other stored data or keyboard data of any kind.

[024] A keyboard 6 is provided on the surface of the card 2, typically bearing the ten numerals, representing the first ten numbers, plus two special symbols such as "star" and "pound". The keyboard is typically arranged in a conventional 3 by 4 manner, as on a telephone tone dial keyboard. The keyboard plan view is further pictured in Figure 5 as element 92.

[025] Within the card 2 are the other requirements for a proximity card, namely a loop antenna, a logic chip, and a source of power, for operating enable/disable/sequencing functions, to be discussed hereinabove. The source of power may be a small battery, or a solar cell. Alternatively, power can be supplied to the card 2 by a reader 60 as will be explained. If the reader 60 provides the power, the entry of the PIN code takes place in close proximity of the reader 60. If a battery or solar cell is used, the PIN code may be entered at any distance from the reader 60.

[026] Figure 2 shows the internal logic 10 of the card 2, and a portion of the reader system 60. The user enters his PIN code in the keyboard 6, labeled as PIN entry 12 in Figure 2. The PIN is known only to the user and to a limited number of personnel, such as the security department.

[027] The entry action initiates a timing cycle in the timer 14, whose purpose will be described later. The data entry via PIN entry 12 is stored in PIN storage 16. Inside the card there is also a reference PIN number stored in storage 18. The reference PIN and user entered PIN are compared in comparator 20. If there is equality of the two values, a signal is emitted on the "enable" line 22 to a data sequencer 44. The function of the enable line 22 and data sequencer 44 will be described later.

[028] There are several categories of data to be transferred from the card to the reader 60. One category is the identification of the card bearer. This ID is typically the employee badge number. The identification data may also contain financial data, especially if this card 2 is also what is known as a credit or a debit card. The identification data may also contain many other factors, such as health data, biometric data, and the authorization level of the user. This identification information is stored in a storage unit 32.

[029] Also desirably transferred from the card 2 to the reader 60 is the PIN itself, from PIN storage element 16. This allows the central station to verify that entry is normal. Also desirably transmitted is the reference PIN data from storage 18, for additional verification of normal function.

[030] A special form of information is that of emergency data. The card user may be under stress, such as illegally being held by a criminal at the point of a knife or a gun. Under these circumstances, the user enters a special code as well as the normal PIN code. Emergency data stored in 34 is reported to the central system via reader 60, by a path described later. Emergency data is sent from the PIN entry keyboard 12 to the emergency data 34 via line 38.

[031] All the data sources 16, 34, 32 and 18 are connected to data bus 40. The bus 40 picks up each digital value from each source and delivers it via line 42 to a data sequencer device 44. The data sequencer 44 energizes one line at a time to each digit of each data source element. This technique is referred to as "serial data transfer" and is well known in the computer art and the security art and is also described in the reference patents, such as References 10 through 15.

[032] The series of digits is next encoded for single line serial transmission, which requires insertion of clocking pulses from clock 50. The mix of clock pulses and data is accomplished with a clock encoder 46. The techniques of clock and data encoding are well known in the computer and data transmission art, and some versions are covered in patent References 1 through 6. A commonly used version is known as "Manchester Encoding". The result is a data stream of pulses of several widths and spacing.

[033] This created logic stream drives a modulator 48. Methods of antenna modulation are known in the art and are covered in References 1 through 6. The modulation modulates the voltage on antenna coil 52.

[034] Card antenna coil 52 is mutually coupled to an antenna 54 in the reader 60. The carrier frequency appears strongly in both coils. Fluctuations in the voltage of either appear as fluctuation in the other, through the fluctuations will be of

differing amplitude. Fluctuations in the card antenna 52, produced by modulation, show up in the antenna loop 54, through the mutual coupling of loop antennas 52 and 54.

[035] The PIN reference is stored in storage 18. The value may be stored during manufacture, or stored on first use by the user, or may be changed at will after use by different types of memory are known in the art. The mechanism for changing the reference PIN is not shown. It may be via the existing keyboard 6, or may be through external contacts on the card, or may be by electromagnetic insertion through a proximity coupling system.

[036] Figure 3 illustrates the functioning of the basic reader 60. The reader 60 function is covered in References 1 through 6, and in other art, but the principle points are now repeated for purposes of completeness. Oscillator 62 excites the system, with its frequency referred to as the carrier frequency. The frequency value in many systems is between 110 and 130 kilohertz, and in another family of systems is 13.56 MHz.

[037] The oscillator 62 drives line 64 to excite coil 54. Coil 54 is mutually coupled to the coil 52 in the card. The coil 52 is repeatedly loaded and unloaded, by the modulator 48, with the data intelligence, as described earlier. At the top of coil 54, which is the same as line 64, there is present both, the carrier frequency and the effects of modulation. The effects of modulation are fluctuations in amplitude. The voltage is amplified by amplifier 66. A detector 68 rectifies the voltage. The act of rectification, which uses diodes and capacitors, is called signal detection. Detection removes the carrier voltage but passes the fluctuations. These fluctuation represent the data from the card. The fluctuations are amplified to the logic pulse level within detector 68, and the clock pulses are removed, in the manner described in the references, leaving a basic string of data pulses on line 70. This data is stored in a data store 72.

[038] In the basic form of the reader, the stored data in 72 is comprised in part of the employee badge number. The employee badge number is compared in comparator 74 with an employee badge number stored in storage 76, also referred to as an authorization code. If the employee badge number from the data source and the

stored employee number match, an authorization signal is emitted on line 78 and sent to an open portal drive 80. Line 82 is energized to open a door, allowing admission of the employee. If the numbers do not match, an alarm is sounded indicating an unauthorized entry attempt.

[039] In slightly more advanced systems, the data from the card 2 is first stored in the data storage unit 72, and then is sent through communication link 84 to a higher level computer system, not shown. This higher level computer system can make a variety of decisions, such as whether or not to ask for another reading, whether to operate an alarm, or check the time of request, and whether there is a user emergency.

[040] The communication link 84 is used when the palm top version, to be described in Figure 5, sends more advanced information such as scheduling data, financial data, letters, memos, or other.

[041] Figures 4 and 5 display a second preferred embodiment, in the form of a hand held or lap top data processor 90, also referred to as computer 90. The hand held computer 90 is also referred to as a "palm toy" or "palm pilot" computer. Hand held "palm top" computers are useful for personal data storage and scheduling, and also for e-mail data processing and data processing in general. Computer 90 has a keyboard 92, a display window 94, and several internal chips. The computer 90 could also represent a cell phone, with its keyboard, and internal battery, and incorporated antenna, although usually minus the display panel.

[042] The circuit elements of an identification and security system, of the dipole radiation type, are incorporated into the palm top computer, for an increase of function with little extra cost. Furthermore, the hand held computer becomes a source of data for the data elements described in the first embodiment, a proximity card, plus other data such as the results of sales calls or computations.

[043] The hand held computer embodiment shown in Figure 5 combines the technology of a palm top computer and the elements antenna 96 and chip 98 of a proximity identification system. The palm top 90 has the keyboard 92, as well as a conventional palm

top screen 94. When the combination 90 is placed near the proximity security system, interacting the antenna 54 of reader 60 of Figure 3, data is transferred from the computer 90 to the communication and computer elements of the security system.

[044] In other words, Figure 5 shows the addition to the palm top 90 of a sensing coil 96 and a chip 98. The chip 98 performs the modulation and data transmission functions of block 10 of Figure 2. The PIN entry 12 of Figure 2 is replaced by the keyboard 92 of Figure 4. The keyboard 92 of the palm top portion of the combination 90 is suitable for entering and verifying the PIN code. The storage elements 16, 34, 32 and 18 may be designed into the chip 98, but for economy, the system would utilize the memory of palm top 90.

[045] The battery which is standard in the hand held computer 90 allows powering of the logic from the battery, thus eliminating the logic power burden generally supplied by proximity coupling, and thus in turn allowing much greater range than for conventional proximity data transmission. That is, data coupling can occur through modulation of the voltage across the coil 54, yet the logic does not have to be powered by proximity coupling at the same time. Furthermore, the battery makes possible energization of the coil 96 on Figure 5 or the coil 54 of Figure 3 with a conventional radio frequency oscillator, and so achieve conventional radio transmission of a greater range. When this invention is utilized in a cell phone, it carries both a dipole antenna and an inductive loop proximity antenna.

[046] Thus, the hand held palm top computer 90, or the cell phone version, serves as a proximity sensed security card 2, also referred to as a credential. It has the built in keyboard 92, equivalent to keyboard 6 in Figure 1, and chip 98, which bears the logic functions shown in Figure 2.

[047] The user carries one less item. The system is secure owing to the PIN entrance requirement. Further, the user now has means for entering data into the central system utilizing security stations, which have previously been useful only for security purposes. The reader 90 has a dual function, that for security and data collection. A population of entry stations is available without the need to establish more stations.

[048] One other precaution is taken against accidental use by the improper person. Referring to Figure 2, after the PIN code is entered and stored in PIN store 16, the card is ready for viable entry. This viable status should not last indefinitely. The timer 14 is energized at the time of data entry and half selects (using the logic definition of half select) the data sequencer 44. The timer 14 will time out after a preset interval, typically one minute, and then prevent further use of the card until a fresh PIN entry function is performed.

[049] The card 6 may also include a simple display, such as LCD or LED. In the palm top version, the screen is already available. The card 6 or combination 90 may contain a speaker for automatic dialing. It may be incorporated into, or be merged with, a variety of palm held devices now on the market.

[050] The amount of time, after a successful PIN code entry, for which the system remains enabled will be determined by the application, such as whether there is simple successful opening of a portal, or whether heavy machinery has to be started, or the quantity of people to be admitted, or the weight and size of equipment to be moved through the portal.

[051] Yet another embodiment of the present invention is illustrated in Figure 6. This embodiment employs the use of a reader 120 having a slot 122 for the insertion of the card 2 shown in Figure 1. This card includes a keyboard 6. Similar to the embodiment shown in Figures 1-3, the user would input his PIN into the card employing the keyboard 6. Circuitry within the card would compare the entered PIN with a PIN stored therein. If a match is successful, when the card 2 is inserted into the slot 122, a device such as the portal 80 would be open. Information is transferred from the card 2 to the system of the present invention through the card reader 120, including a signal denoting a successful match employing contacts for magnetic bit sensors. Alternatively, a convention swipe-type reader may be employed in which a magnetic stripe (not shown) provided on the card would be read by one or more magnetic sensors within the slot of the swipe reader.

[052] A successful match would also enable various other operations to be performed. For example, as shown in Figure 7, a successful match would create a signal on line 114 which would operate a solenoid 100 or a relay 104. The solenoid 100 would cause a mechanical action to occur at 102 and the relay 104 would cause an electrical action to occur at 106. Additionally, the successful match would result in a switch 108 to activate a piece of equipment 110.

[053] Another embodiment shows the use of the technology of the present invention to safely operate a firearm. Although this embodiment could be utilized with the card and card reader shown in Figure 6, it would more likely be utilized with the proximity card shown in Figures 1-3, as well as the system illustrated in Figure 7. In this embodiment, a firearm 112 would include the proximity sensor shown in Figure 3. After the user has entered his PIN by the keyboard 6 and a successful match has been determined, a signal would be sent from the card 6 to the reader 60, thereby unlocking the safety latch on the firearm. Therefore, only the authorized bearer of the firearm, having knowledge of the PIN, would be capable of releasing the safety latch.

[054] While the present invention has been described by means of several embodiments, the invention is not limited thereto, for obvious modifications will occur to those skilled in the art without departing from the spirit and scope of the invention.